



TAURI7



1. Compact Solution

7inch screen size diagonal.



2. Software Flexibility

Software compatible with full series of TAURI products including 7inch, 10inch,15.6inch and 21.5inch.



3. IP65 Front Glass WaterProof





4. Anti-glare glass to eliminate reflections



5. Dual Camera

For higher security and accuracy to recognize a human face.



6. High temperature alarm

An alarm with sound to alert users that runs a high temperature.



7. Customizable Screen Saver Videos

- Free Advertising

Options to play customized videos when no scans are performed on TAURI. This allows companies to promote their brand/products with a personalized message.

WWW.SMARTHOMEGCC.COM

TAURI OTA







8. Constant Feature Updates

TAURI is designed, developed and manufactured by GloryStar. We provide constant software features upgrade for TAURI.



11. Face Detection

Facial detection is a technology that differentiates a human face from other objects.

- i. It can provide a reminder alert if a person is not protected with a facial mask this is an optional feature in settings.
- ii. Taking a snapshot of someone who runs a high temperature and send an email notification - this feature is optional in settings

9. Access Control

It can be synced with automatic doors through relays to restrict entry access to people who run at a high temperature.



12. Optional Face Recognition

i. Recognize employees - employees can voluntarily take a photo of themselves to be locally stored in TAURI for employee/guest recognition for increased security

ii. If an employee runs a high temperature, time and location is marked and an email alert is sent to facilitate tracking and decrease the spread of infection.



Infrared Temperature sensor made in Germany.



13. RFID Card Access (coming soon)

Connect with RFID card to control door opening.



TAURI7 Specification

Model		TAURI7
Display	Panel Size	7"
	Brightness	400nits
	Resolution	800 x 1280
Hardware	Processor	Quad Core A35
	RAM	2GB
	Storage	8GB
Operating System	OS	Android 8.1
Software	TAURI features	Define temperature range for alert
		Adjust volume of alert sound
		OTA Feature Update
		Heat Map Generation
		Multi Language support
		Face Detection Optional Face Recognition
Connectivity	Wifi	2GHz + 5GHz
	Bluetooth	EDR 4.0
		EM4100, Mifare s50 S70,
	RFID	Desfire, FM1208
	Ethernet	RJ45 10/100PoE
	Digital I/O	Relay x 2, RS485 x 1, RS232 x 1
	USB	Micro USB x 1
Multimedia	Microphone	Echo cancelling mic
	Speaker	Waterproof speaker, 2W x 1
	Camera	Dual Camera 1 RGB, 1 Infrared
	Sensor	Proximity sensor; Ambient sensor;
Sensor	Lighting	White
	Monitor	Watchdog for device status
Mounting	Mounts	Wall Mount, Table Stand (additional cost) or Floor Stand (additional cost)
Power	Consumption	12W
	Power supply	Either 12V DC or POE
Infrared Temperature	Power input	3.3 – 3.6V, 50mA, USB connect
Sensor	Temperature check distance	0.5m – 1m
	Temperature check range	-45°C - 30°C
	Temperature check error	±0.3°C
Dimension	Size (mm)	230 x 112 x 40
	Weight (kg)	1.5KG
	Gift Box Dimension (mm)	405 x 208 x 127
	Gift Box Weight	2KG(without bracket)
	PCs per Master Carton	6 pcs
		OVC(viith authorith and lot)
	Master carton weight (kg) Master carton dimension (mm)	9KG(without bracket)

HOW TO BUY

WWW.SMARTHOMEGCC.COM